



## TRANSPORTATION SPECS - All Terrain Cranes

### GROVE MODEL GMK6220 - 220 TON CAPACITY

<u>COMPONENT WEIGHTS</u>	<u>LBS.</u>	<u>KGS.</u>	<u>JIB COMPONENT WEIGHTS</u>	<u>LBS.</u>	<u>KGS.</u>
Complete Crane 6 axle carrier incl. Blocks, ball, jib and max. counterweight	292,414	132 674	Bifold Swingaway Extension 43' – 72' (13m – 22m) 4' □	6,000	2 722
Crane c/w jib, blocks, ball and w/o counterweight	153,614	69 674	Base Section 43'		
Main Unit w/o blocks, ball, jib and counterweight	141,028	63 980	Tip Section 30'		
Counterweight Max.	138,800	63 000			
<b><u>ADDITIONAL INFORMATION</u></b>					
160 Ton Block (7 Sheave)	3,860	1 750			
80 Ton Block (3 Sheave)	2,050	950			
12 Ton Ball	676	307			
Swingaway (43' – 72') Bifold Extension 4' □	6,000	2 722			
Front Outrigger Beams & Jacks	5,357	2 431			
Rear Outrigger Beams & Jacks	5,919	2 686			
Boom Assembly (w/o lift cylinder)	44,908	20 376			
Lift Cylinder	4,475	2 030			
Tire Size 20.5R25 (12 total) each	809	367			
Main Load Line 7/8" x 984' (22mm x 300m)	1,397	367			
Auxiliary Hoist Line 7/8" x 755' (22mm x 230m)	1,072	485			
<b><u>TRANSPORTATION</u></b>					
Maximum Speed:	60 km/hr 37.5 mph				
<b>All Provinces / States / All Seasons</b>	<b><u>NO.</u></b>	<b><u>Trailer</u></b>			
0 lb. Counterweight + Misc.	1	Tandem			
9,700 lb. Counterweight + Misc.	1	Tandem			
28,600 lb. Counterweight + Misc.	1	Tandem			
94,700 lb. Counterweight + Misc.	2	Tridem			
138,800 lb. Counterweight + Misc.	3	Tridem			

