



TRANSPORTATION SPECS - Crawler Cranes MANITOWOC MODEL M12000 - 120 TON CAPACITY

<u>COMPONENT WEIGHTS</u>	<u>LBS.</u>	<u>KGS.</u>	<u>MAIN BOOM 50' TO 120'</u> <u>5'6" X 5'7"</u>	<u>LBS.</u>	<u>KGS.</u>
Complete Crane C/W 50' Main Boom 76,280 lb. Main Cwt, 14,300 lb. Carbody Cwt	220,300	99 900			
			Butt Section 25'	4,927	2 235
			Insert 10'	840	380
Superstructure, carbody and tracks (51'9" x 11'6" x 11'8")	130,000	58 967	Insert 20'	1,445	655
			Insert 40'	2,635	1 195
Crawlers (22'3" x 2'11" x 3'9") 2 pcs.	26,301	11 930	Tip Section 25'	3,360	1 525
<u>COUNTERWEIGHTS</u>					
76,280 lb. Upper Cwts					
1 – A Cwt (14'6" x 3'11" x 2'9") each	25,573	11 600			
2 – B Cwt (4'9" x 3'10" x 2'11") each	12,676	5 750			
2 – C Cwt (4'9" x 3'10" x 2'11") each	12,676	5 750			
14,300 lb. Carbody Cwts					
1 – Carbody with float (6'10" x 4'2" x 2'2") each	7,319	3 320			
1 – Carbody w/o float (6'10" x 2'8" x 2'2") each	7,165	3 250			
<u>ADDITIONAL INFORMATION</u>					
90 Ton/81 mT Hook Block, 3 Sheave	3,996	1 813			
13.6 mT Ball	1,310	594			

STERLING CRANE

Outline dimensions

